


电机参数 Motor Data

电机型号	Motor model			SR308112G	SR308124G	SR308136G	SR308148G
1 额定电压	Nominal voltage	V	V	12	24	36	48
2 空载转速	No load speed	rpm	Wnl	7900	8380	8500	8490
3 空载电流	No load current	mA	InI	350	170	150	100
4 额定转速	Nominal speed	rpm	Wc	7470	7600	7500	7690
5 额定转矩	Nominal torque	mNm	Tc	51.6	85.6	86.6	89.7
6 额定电流	Nominal current	A	Ic	3.58	3.15	2.17	1.66
7 输出功率	Output power	W	Pc	40	68	69	72
8 堵转转矩	Stall torque	mNm	Tmax	865.2	669	781	918.9
9 堵转电流	Stall current	A	Imax	60	24.6	19.6	17.08
10 最大效率	Max. efficiency	%	ηmax	90	80	85	88
11 线间电阻	Terminal resistance	Ω	Rt	0.2	0.71	1.84	2.81
12 力矩系数	Torque constant	mNm / A	Kt	14.4	27.2	39.9	53.8
13 速度常数	Speed constant	rpm / V	Kn	663	349	239	177.5
14 速度扭矩比	Speed torque gradient	rpm / mNm	Δn / ΔT	8.3	9.1	11	8.9
15 线间电感	Terminal inductance	mH	L	0.036	0.23	0.48	0.588
16 转子转动惯量	Rotor inertia	gcm ²	J	34.4	34.2	34.2	35.2

特性参数 Specifications

1 环境温度 ambient temperature	Ta	-30~+100 °C
2 最大允许线圈温度 max. winding temperature	Tcoilmax	+125°C
3 最大允许速度 max. speed	Nmax	9350rpm
4 轴向窜动 axial play	Δt	0.05-0.15 mm
5 极对数 number of pole pairs	2p	1
6 换向器片数 number of commutator segments		13
7 马达重量 weight of motor	Wt	274 g
8 最大轴向载荷 (动态) Max. axial load (dynamic)		5.6N
9 最大允许安装力 (静态) Max. force for press fits (static)		110N
10 最大径向载荷 (离法兰4mm处) Max. radial load, 4 mm from flange		28N

电机运行范围 Operating Range



接线定义 Terminal definitions

