





电机参数 Motor Data

1 电机型号	Motor model			SBR367824B	SBR367836B	SBR367848B	
2 额定电压	Nominal voltage	V	V	24	36	48	
3 空载转速	No load speed	rpm	Wnl	31300	31360	31200	
4 空载电流	No load current	mA	InI	<200	<110	<100	
5 额定转速	Nominal speed	rpm	Wc	25140	27000	28220	
6 额定转矩	Nominal torque	mNm	Tc	58.4	60	51	
7 额定电流	Nominal current	A	Ic	8	5.5	3.5	
8 输出功率	Output power	W	Pc	154	170	151	
9 堵转扭矩	Stall torque	mNm	Tmax	1251	2072	1130	
10 堵转电流	Stall current	A	Imax	171.4	190.1	77.4	
11 最大效率	Max. efficiency	%	ηmax	80	86	90	
12 线间电阻	Terminal resistance	Ω	Rt	0.14	0.33	0.62	
13 线圈电感	Terminal inductance	L	mH	0.042	0.06	0.33	
14 力矩系数	Torque constant	mNm / A	Kt	7.3	10.9	14.6	
15 速度常数	Speed constant	rpm / V	Kn	1305.6	872	650.8	
16 速度扭矩比	Speed torque gradient	rpm / mNm	Δn / ΔT	105.5	72.7	58.4	

特性参数 Specifications

1 环境温度 ambient temperature	Ta	-20~+65 °C
2 最大允许线圈温度 max. winding temperature	Tcoilmax	+85 °C
3 最大允许速度 max. speed	Nmax	31360rpm
4 轴向窜动 axial play	Δt	0.05-0.15 mm
5 极对数 number of pole pairs	2p	1
6 换向器片数 number of commutator segments		3
7 马达重量 weight of motor	Wt	373g
8 最大轴向载荷 (动态) Max. axial load (dynamic)		5N
9 最大允许安装力 (静态) Max. force for press fits (static)		98N
10 最大径向载荷 (离法兰4mm处) Max. radial load, 4 mm from flange		25N

电机运行范围 Operating Range



Terminal definitions

Green	U	1 +5V	Magnet Encoder 3 Channel 1000CPT
Black	V	2 GND	
Red	W	3 Channel A-	
		4 Channel A+	
		5 Channel B-	
		6 Channel B+	
		7 Channel Z-	
		8 Channel Z+	
		9 Hall3	
		10 Hall2	
		11 Hall1	